

// 702AA



EVOLUTION

气动播种机

内胶层: 黑色导电NR

加强层: 高强度纤维线并嵌有螺旋钢丝

外层: 黑色 NBR/PVC – 耐油、耐热、耐磨损、耐臭氧

应用: 气动播种设备中的农作物种子输送

常规运行温度范围: $-30^{\circ}\text{C} + 80^{\circ}\text{C}$ ($-22^{\circ}\text{F} + 176^{\circ}\text{F}$)

↔		↔		⬇		⬆		⚖		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
32,0	1 1/4"	43,00	1,69	10	150	30	450	64	2,52	100	0,880	0,60
38,0	1 1/2"	49,00	1,93	10	150	30	450	76	2,99	100	1,030	0,70
45,0	1 3/4"	56,00	2,20	10	150	30	450	90	3,54	100	1,190	0,80
51,0	2"	62,00	2,44	10	150	30	450	102	4,02	100	1,330	0,90
63,0	2 1/2"	76,00	2,99	10	150	30	450	189	7,44	90	2,210	1,49
76,0	3"	89,00	3,50	10	150	30	450	228	8,98	90	2,430	1,64