

S-468 OH

液态食品吸排管 - PVC - 恶劣工况

FDA EU 10/2011 A+B+C AS 2070



具有不含邻苯二甲酸酯等塑化剂的认证

结构: 透明 PVC - 耐磨损、耐臭氧

加强层: 红色抗震硬质 PVC

应用: 液态食品和酒精度不超过 20% 的酒精饮料的吸排, 用 5% 的苏打水消毒

安全系数: 3:1

温度范围: -5 °C +60 °C (+23 °F +140 °F)

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
468OH025004M60	25	1			400	7	100	90	125	20/50	50
468OH030004M60	30	1 3/16			500	7	100	90	150	50	50
468OH032004M60	32	1 1/4			520	7	100	90	160	20/50	50
468OH038004M60	38	1 1/2			730	7	100	90	190	20/50	50
468OH040004M60	40	1 9/16			750	7	100	90	200	50	50
468OH051004M60	51	2			1000	7	100	90	255	20/50	50
468OH060004M60	60	2 3/8			1450	7	100	90	300	50	50
468OH063004M60	63	2 1/2			1500	6	90	90	315	50	50
468OH070004M6Z	70	2 3/4			1560	5	75	90	350	50	50
468OH076004M60	76	3			1900	5	75	90	380	20/50	50
468OH080004M60	80	3 1/8			2100	5	75	90	400	50	50
468OH102004M60	102	4			3300	4	60	90	510	20	20
468OH120004M6Z	120	4 3/4			3600	3	45	80	600	20	20