

AGI--INDUSTRIAL HOSE DIV.
ALFAGOMMA GROUP

**TECHNICAL DATA
SHEET**

DATE : 07/04/2017

										
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
6	1/4	13	0,51	20	300				0,130	0,087
8	5/16	15	0,59	20	300				0,160	0,110
10	3/8	17	0,67	20	300				0,190	0,130
13	1/2	21	0,83	20	300				0,270	0,180
16	5/8	25	0,98	20	300				0,360	0,245
19	3/4	29	1,14	20	300				0,460	0,310
25	1	35	1,38	20	300				0,580	0,390
NA		LA		NEU		EMEA		SA	AP	AU



976AB

General purpose 20 bar (300 psi) - EPDM

Tube: Black conductive EPDM

Reinforcement: High tensile textile cords

Cover: Grey EPDM - abrasion and ozone resistant

Use: Air, water and mild chemicals delivery in general industrial applications

Safety factor: 3:1

Temperature: -40 °C +100 °C (-40 °F +212 °F)

WE HEREBY DECLARE THAT THE ALFAGOMMA HOSE 976AB CAN BE USED WITH TEMPERATURES FROM -40° C (-40°F) UP TO 100° C (212°F) WITH PEAKS UP TO 120°C (248°F)

QUALITY MANAGER

Antonio Piccinini

ALFA GOMMA INDUSTRIAL S.p.A.

Head Office: Via Attilio Di Sante, snc - Nucleo Industriale - 64100 Sant'Atto (TE) ITALY - Tel. +39.0861.442.1 - Fax +39.039.6287.500

Sales & Marketing: Via Torri Bianche, 1 - 20871 Vimercate (MB) ITALY - Tel. +39.039.6016.1 - Fax +39.039.62.87.279

info@alfagomma.it - www.alfagomma.com

Capitale Sociale € 4.672.000,32 i.v. - REA Teramo N° 92225 - C.F. e P.IVA N° IT 00730430675