

## // AUTOLOCK MULTIPLE COLOURS

### MAIN FEATURES

- ▲ SMOOTH COVER
- ▲ OPTIMUM PERFORMANCE
- ▲ FLAME RESISTANCE
- ▲ EASY ASSEMBLY
- ▲ COMPATIBLE WITH PUSH-ON FITTINGS



### MAIN APPLICATIONS

- // MACHINE TOOLS
- // PAPER INDUSTRY
- // INJECTION MOULDING MACHINE
- // TRANSFER LINES
- // PET BLOW FORMING MACHINES
- // ROBOT AND AUTOMATION



## // AUTOLOCK MULTIPLE COLOURS COVER



**Tube:** oil resistant synthetic rubber.

**Reinforcement:** one high tensile textile braid.

**Colours:** red, blue, yellow, green (non conductive).

**Cover:** smooth up to 1", abrasion, ozone and hydrocarbon resistant synthetic rubber.

**MSHA APPROVED**

**Application:** low pressure hydraulic lines, fuel oil, antifreeze solutions, air and water. Compatible with PUSH ON fittings.

**Constant operation:** -40 °C +100 °C (-40 °F +212 °F)  
air max T = +70 °C (+160 °F)

**Safety factor:** 1:4

**Length:** random

| Item code |      |      |      |       |      |     |     |      |      |     |      |       |       |
|-----------|------|------|------|-------|------|-----|-----|------|------|-----|------|-------|-------|
|           | Dash | mm   | in   | mm    | in   | Mpa | psi | Mpa  | psi  | mm  | in   | kg/m  | lb/ft |
| 8K7AH06   | 04   | 6,0  | 1/4" | 12,00 | 0,47 | 2,8 | 400 | 11,2 | 1625 | 65  | 2,56 | 0,106 | 0,07  |
| 8K7AH10   | 06   | 10,0 | 3/8" | 15,70 | 0,62 | 2,8 | 400 | 11,2 | 1625 | 75  | 2,95 | 0,150 | 0,10  |
| 8K7AH12   | 08   | 13,0 | 1/2" | 18,80 | 0,74 | 2,8 | 400 | 11,2 | 1625 | 100 | 3,94 | 0,203 | 0,14  |
| 8K7AH16   | 10   | 16,0 | 5/8" | 23,20 | 0,91 | 2,4 | 350 | 9,6  | 1400 | 125 | 4,92 | 0,268 | 0,18  |
| 8K7AH19   | 12   | 19,0 | 3/4" | 27,20 | 1,07 | 2,1 | 300 | 8,4  | 1200 | 150 | 5,91 | 0,401 | 0,27  |
| 8K7AH25   | 16   | 25,0 | 1"   | 33,50 | 1,32 | 1,7 | 250 | 6,8  | 1000 | 203 | 7,99 | 0,493 | 0,33  |

## // AUTOLOCK BLACK COVER



**Tube:** oil resistant synthetic rubber.

**Reinforcement:** one high tensile textile braid.

**Colours:** black (conductive) hose color provides additional UV resistant.

**Cover:** smooth up to 1", abrasion, ozone and hydrocarbon resistant synthetic rubber.

**MSHA APPROVED**

**Application:** low pressure hydraulic lines, fuel oil, antifreeze solutions, air and water. Compatible with PUSH ON fittings.

**Constant operation:** -40 °C +100 °C (-40 °F +212 °F)  
air max T = +70 °C (+160 °F)

**Safety factor:** 1:4

**Length:** random

| Item code |      |      |      |      |      |     |     |      |      |     |      |       |       |
|-----------|------|------|------|------|------|-----|-----|------|------|-----|------|-------|-------|
|           | Dash | mm   | in   | mm   | in   | Mpa | psi | Mpa  | psi  | mm  | in   | kg/m  | lb/ft |
| 8K7AA06   | 04   | 6,0  | 1/4" | 13,2 | 0,52 | 2,8 | 400 | 11,2 | 1625 | 65  | 2,56 | 0,127 | 0,09  |
| 8K7AA10   | 06   | 10,0 | 3/8" | 16,9 | 0,67 | 2,8 | 400 | 11,2 | 1625 | 75  | 2,95 | 0,178 | 0,12  |
| 8K7AA12   | 08   | 13,0 | 1/2" | 20,0 | 0,79 | 2,8 | 400 | 11,2 | 1625 | 100 | 3,94 | 0,234 | 0,16  |
| 8K7AA16   | 10   | 16,0 | 5/8" | 24,4 | 0,96 | 2,4 | 350 | 9,6  | 1400 | 125 | 4,92 | 0,337 | 0,23  |
| 8K7AA19   | 12   | 19,0 | 3/4" | 28,4 | 1,12 | 2,1 | 300 | 8,4  | 1200 | 150 | 5,91 | 0,435 | 0,29  |
| 8K7AA25   | 16   | 25,0 | 1"   | 34,7 | 1,37 | 1,7 | 250 | 6,8  | 1000 | 203 | 7,99 | 0,600 | 0,40  |