

**HYDRAULIC HOSE DIVISION
ALFAGOMMA GROUP****DECLARATION OF
CONFORMITY**

DATE: 20/06/2022

**HIGH PRESSURE HYDRAULIC LINES APPLICATION, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND
WATER.****TEMPERATURE -40 °C +100 °C (-40 °F +212 °F), T_{AIR MAX} = +70 °C (+160 °F)****ALFAGOMMA AUTOLOCK BLACK COVER****Fire Retardant Anti Static (FRAS) approved****APPLICATION:**

LOW PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER. COMPATIBLE WITH PUSH ON FITTINGS.

TUBE:

OIL RESISTANT SYNTHETIC RUBBER.

REINFORCEMENT:

ONE HIGH TENSILE TEXTILE BRAID.

COVER:

ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER.

STANDARD BRAND:

INKJET - WHITE LETTERING

“ <AG> ALFAGOMMA – AUTOLOCK 1/2” WP 400 PSI FLAME RESISTANT MSHA IC 152/16 FRAS <_QYY> - <BATCH #> - <DATE> ”

NORMS:

ALFAGOMMA SPECIFICATION

TECHNICAL DATA

Product Code	Internal Diameter (mm)	Outside Diameter (mm)	Minimum Working Pressure (Mpa)	Minimum Burst Pressure (MPa)	Minimum Bend Radius (mm)	Weight (kg/m)
8K7AA01200F2L8	12,0	20,0	2,8	11,2	100,0	0,234

WE HEREBY DECLARE THAT THE GOODS SUPPLIED CONFORM TO STANDARD NORMS REQUIREMENT.

(TZYY HWANG LEW)

FACTORY QUALITY MANAGER**ALFAGOMMA MALAYSIA SDN BHD**

PLO 344, JALAN PERAK 4, PO BOX 97, 81707 PASIR GUDANG, JOHOR, MALAYSIA

TEL (60) 251 0852 – FAX (60) 251 0408

E-mail: alfagomma@alfagomma.com.my