

// WATERBLAST HOSE

WATERBLAST


// WATERBLAST - WB10L



Tube: oil and water resistant synthetic rubber.

Reinforcement: four high tensile steel spirals.

Cover: oil, water and ozone resistant synthetic rubber.

Application: very high pressure water jetting.

Constant operation: -10 °C +70 °C (14 °F +158 °F)

Safety factor: 2,5:1

Length: see below grid for the multiples.

Item Code														Length
	Dash	mm	in	mm	in	Mpa	psi	Mpa	psi	mm	in	kg/m	lb/ft	m
1003795	08	13,0	1/2"	13,00	0,51	70,0	10000	175,0	25000	200,0	7,87	0,805	0,55	15,250
1003796	08	13,0	1/2"	13,00	0,51	70,0	10000	175,0	25000	200,0	7,87	0,805	0,55	20,000
1004044	12	19,0	3/4"	32,20	1,27	70,0	10000	175,0	25000	210,0	8,27	1,450	0,98	15,250
1004212	12	19,0	3/4"	32,20	1,27	70,0	10000	175,0	25000	210,0	8,27	1,450	0,98	20,000
1004213	16	25,0	1"	38,70	1,52	70,0	10000	175,0	25000	320,0	12,60	1,981	1,34	15,250
1004214	16	25,0	1"	38,70	1,52	70,0	10000	175,0	25000	320,0	12,60	1,981	1,34	20,000

// WATERBLAST - WB15L



Tube: oil and water resistant synthetic rubber.

Reinforcement: four high tensile steel spirals.

Cover: oil, water and ozone resistant synthetic rubber.

Application: very high pressure water jetting.

Constant operation: -10 °C +70 °C (14 °F +158 °F)

Safety factor: 2,5:1

Length: see below grid for the multiples.

Item Code														Length
	Dash	mm	in	mm	in	Mpa	psi	Mpa	psi	mm	in	kg/m	lb/ft	m
1003471	06	10,0	3/8"	21,40	0,84	124,0	18000	310,0	45000	150,0	5,91	0,850	0,58	15,250
1003470	06	10,0	3/8"	21,40	0,84	124,0	18000	310,0	45000	150,0	5,91	0,850	0,58	20,000
1003473	08	13,0	1/2"	24,40	0,96	110,0	16000	275,0	40000	200,0	7,87	1,120	0,76	15,250
1003472	08	13,0	1/2"	24,40	0,96	110,0	16000	275,0	40000	200,0	7,87	1,120	0,76	20,000
1003475	12	19,0	3/4"	32,00	1,26	100,0	14500	250,0	36000	280,0	11,02	1,683	1,14	15,250
1003474	12	19,0	3/4"	32,00	1,26	100,0	14500	250,0	36000	280,0	11,02	1,683	1,14	20,000