

// 340AH



EXTRUDED
TUBE

蒸汽软管 18 bar (270 psi) - 钢丝编织

内胶层: 黑色导电EPDM

加强层: 高强度钢丝编织

外层: 红色EPDM - 耐热、耐磨损、耐臭氧- 表面刺孔

应用: 饱和或过热蒸汽

常规运行温度范围: $-40^{\circ}\text{C} + 210^{\circ}\text{C}$ ($-40^{\circ}\text{F} + 410^{\circ}\text{F}$)

间歇可承受最高温度 232°C (450°F)

推荐接头:

- 磨口连接密封式接头
- 液压接头, 请参考ALFAGOMMA液压产品目录

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	23,00	0,91	18	270	180	2610	130,0	5,12		0,400	0,27
16,0	5/8"	26,00	1,02	18	270	180	2610	160,0	6,30		0,480	0,33
19,0	3/4"	31,00	1,22	18	270	180	2610	190,0	7,48		0,740	0,50
25,0	1"	38,00	1,50	18	270	180	2610	250,0	9,84		0,900	0,61
32,0	1 1/4"	46,00	1,81	18	270	180	2610	320,0	12,60		1,190	0,80
38,0	1 1/2"	52,00	2,05	18	270	180	2610	380,0	14,96		1,340	0,91
51,0	2"	67,00	2,64	18	270	180	2610	510,0	20,08		2,130	1,44
63,0	2 1/2"	81,00	3,19	18	270	180	2610	630,0	24,80		2,990	2,01
76,0	3"	94,00	3,70	18	270	180	2610	760,0	29,92		3,970	2,67