

// 341AH



EXTRUDED
TUBE

蒸汽软管 18 bar (270 psi) - CIIR - 钢丝编织

内胶层: 黑色导电氯化丁基橡胶

加强层: 高强度钢丝编织

外胶层: 红色EPDM - 耐热、耐磨损、耐臭氧-表面刺孔

应用: 饱和或过热蒸汽

常规运行温度范围: -40°C $+210^{\circ}\text{C}$ (-40°F $+410^{\circ}\text{F}$)

间歇可承受最高温度 232°C (450°F)

推荐接头:

- 磨口连接密封式接头
- 液压接头, 请参考ALFAGOMMA液压产品目录

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	23,00	0,91	18	270	180	2610				0,400	0,27
19,0	3/4"	31,00	1,22	18	270	180	2610				0,720	0,49
25,0	1"	38,00	1,50	18	270	180	2610				0,880	0,60
32,0	1 1/4"	46,00	1,81	18	270	180	2610				1,170	0,79
38,0	1 1/2"	52,00	2,05	18	270	180	2610				1,330	0,90
51,0	2"	67,00	2,64	18	270	180	2610				2,040	1,38