

// 648AA



ABS



钻井平台补给管 软壁 – 燃油 – 液态泥浆 20 bar (300 psi)

内胶层: 黑色导电NBR

加强层: 高强度纤维线–防静电线

外胶层: 黑色导电CR –耐磨损、耐臭氧、耐烃类化合物和耐火

应用: 将燃油和液态泥浆从平台补给船输送到海工平台

也适用于海水泵送和散装物料的输送

抗拉强度:

ID 2" 2.000 kg

ID 3" 4.000 kg

ID 4" 7.000 kg

ID ≥ 5" 10.000 kg

软管总成可具备ABS船级社产品证书

连续导电

常规运行温度范围: -30 ° C +90 ° C (-22 ° F +194 ° F)

推荐接头:

- 带预扣压套筒的NPT外螺纹的软管接头
- ASA150标准的固定法兰或松套法兰软管接头

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	67,00	2,64	20	300	80	1200	300,0	11,81		1,890	1,28
76,0	3"	94,00	3,70	20	300	80	1200	456,0	17,95		2,950	1,99
102,0	4"	120,00	4,72	20	300	80	1200	612,0	24,09		3,950	2,66
127,0	5"	147,00	5,79	20	300	80	1200	762,0	30,00		5,640	3,80
152,0	6"	176,00	6,93	20	300	80	1200	912,0	35,91		8,030	5,40