

// BOP - FIRESAFE 5000



MSHA

LLOYD'S

API 16D – 耐火

内胶层: 耐油合成橡胶,

加强层: 四层/六层高强度钢丝缠绕,

外胶层: 耐油、耐火红色合成橡胶

应用: 防喷器系统中的高压液压管线, 确保火灾产生时在一定时间内防喷器控制系统仍能正常工作。

常规运行温度范围: -40℃~+121℃ (-40~+250℉)

长度: 内径1"及以下, 不定长; 1 1/4"及以上, 最长到61m

软管总成具备英国劳氏 (LR) 船级社产品证书

推荐接头:

- 液压接头—API螺纹

Item Code	Const.	↔			↔		↔		↔		↔		↔	
		Dash	mm	in	mm	in	Mpa	psi	Mpa	psi	mm	in	kg/m	lb/ft
1001250	4WS	06	10,0	3/8"	28,10	1,11	35,0	5000	140,0	20000	180,0	7,09	1,134	0,77
1001244	4WS	08	13,0	1/2"	31,00	1,22	35,0	5000	140,0	20000	230,0	9,06	1,280	0,87
1001249	4WS	12	19,0	3/4"	38,80	1,53	35,0	5000	140,0	20000	300,0	11,81	1,860	1,26
1001243	4WS	16	25,0	1"	46,00	1,81	35,0	5000	140,0	20000	340,0	13,39	2,690	1,81
1001247	4WS	20	32,0	1 1/4"	53,10	2,09	35,0	5000	140,0	20000	460,0	18,11	3,340	2,25
1001246	6WS	24	38,0	1 1/2"	64,90	2,56	35,0	5000	140,0	20000	560,0	22,05	5,870	3,95
1001248	6WS	32	51,0	2"	78,70	3,10	35,0	5000	140,0	20000	700,0	27,56	7,780	5,23