

// 6J511 EN



燃油吸排管 10 bar (150 psi) - 一般工况 EN 13765 - arrêté TMD

内层钢丝: 镀锌钢丝线

内层: 聚丙烯薄膜

外层: 带有纵向黄条纹的灰色PVC镀层织物

外层钢丝: 镀锌钢丝

应用: 燃油吸排

专为罐式车设计

安全系数: 4:1

常规运行温度范围: -30°C $+80^{\circ}\text{C}$ (-22°F $+176^{\circ}\text{F}$)

可通过软管两端的两根金属丝与接头的接触来确保其连续导电性

电阻: $\leq 2.5 \text{ Ohm/mt}$ ($\leq \text{DN } 50\text{mm}$ (2"))

$\leq 1 \text{ Ohm/mt}$ ($> \text{DN } 50\text{mm}$ (2"))

推荐接头:

- 复合软管接头

										
mm	in	mm	in	bar	psi	mm	in	%	kg/m	lb/ft
25	1"	37	1,46	10	150	100	4,00	90	1,300	0,873
40	1 1/2"	52	2,05	10	150	140	5,50	90	2,000	1,343
50	2"	61	2,40	10	150	150	6,00	90	2,100	1,410
65	2 5/8"	88	3,46	10	150	175	6,00	90	2,200	1,477
80	3 1/8"	93	3,66	10	150	250	10,00	90	2,700	1,810
100	4"	119	4,69	10	150	350	14	90	4,000	2,686