

										
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
19	3/4	31	1,22	10	150	57	2,25	100	0,740	0,500
25	1	37	1,46	10	150	75	3,00	100	0,920	0,620
32	1 1/4	44	1,73	10	150	96	3,75	100	1,090	0,735
38	1 1/2	50	1,97	10	150	114	4,50	100	1,270	0,855
51	2	63	2,48	10	150	153	6,00	100	1,640	1,105
63	2 1/2	75	2,95	10	150	189	7,50	90	2,150	1,445
76	3	88	3,46	10	150	228	9,00	90	2,580	1,735
102	4	116	4,57	10	150	306	12,00	90	3,580	2,410
NA		LA	NEU	EMEA	SA	AP	AU			



405LE

脂肪类食品吸排管 10 bar (150 psi)

FDA D.M. 21/03/73

内胶层: 白色 NBR

加强层: 两层高强度纤维线并嵌有螺旋钢丝

外胶层: 蓝色 NBR/PVC - 耐磨损、耐臭氧、耐油

应用: 液态食品、脂肪类食品和酒精度不超过 75% 的酒精饮料的吸排
用 130 °C (266 °F) 水蒸气消毒 30 分钟或直接用 5% 的苏打水消毒

安全系数: 3:1

温度范围: -30 °C +100 °C (-22 °F +212 °F)