

										
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
19	3/4	29	1,14	2	30	57	2,25	100	0,650	0,440
22	7/8	32	1,26	2	30	66	2,75	100	0,730	0,495
25	1	35	1,38	2	30	75	3,00	100	0,820	0,555
28	1 1/8	38	1,50	2	30	84	3,25	100	0,880	0,595
35	1 3/8	45	1,77	2	30	105	4,25	100	1,040	0,700
38	1 1/2	48	1,89	2	30	114	4,50	100	1,120	0,755
40	1 9/16	50	1,97	2	30	120	4,75	100	1,170	0,790
42	1 5/8	52	2,05	2	30	126	5,00	100	1,210	0,815
45	1 3/4	55	2,17	2	30	135	5,25	100	1,290	0,870
48	1 7/8	58	2,28	2	30	144	5,75	100	1,360	0,915
51	2	61	2,40	2	30	153	6,00	100	1,460	0,985
57	2 1/4	67	2,64	2	30	171	6,75	100	1,610	1,085
60	2 3/8	70	2,76	2	30	180	7,00	90	1,860	1,250
63	2 1/2	73	2,87	2	30	189	7,50	90	1,940	1,305
76	3	86	3,39	2	30	228	9,00	90	2,270	1,530
90	3 1/2	100	3,94	2	30	270	10,50	90	2,840	1,910
102	4	112	4,41	2	30	306	12,00	90	3,140	2,115
115	4 1/2	127	5,00	2	30	345	13,50	90	4,040	2,720
127	5	141	5,55	2	30	381	15,00	80	4,520	3,040
NA		LA		NEU		EMEA		SA	AP	AU



616AA

船用燃料输送管 - 硬壁

ISO 7840/A2 SAE J1527/A2 SAE 20R3/C
94/25/CE 2003/44/EC

内胶层: 黑色 NBR - 耐油、耐火

加强层: 两层高强度纤维线并嵌有螺旋钢丝

外胶层: 黑色 NBR/PVC - 耐磨损、耐臭氧、耐烃类化合物和耐火

应用: 船用燃料输送, 超柔, 抗极度扭曲, 也适用于海水排放

安全系数: 5:1

温度范围: -20 °C +100 °C (-4 °F +212 °F)