

										
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
19	3/4	33	1,30	10	150				0,710	0,480
19	3/4	35	1,38	10	150				0,830	0,560
25	1	40	1,57	10	150				0,870	0,585
32	1 1/4	48	1,89	10	150				1,240	0,835
38	1 1/2	55	2,17	10	150				1,650	1,110
40	1 9/16	60	2,36	10	150				1,930	1,300
51	2	71	2,80	10	150				2,400	1,615

19	3/4	38	1,50	10	150				1,000	0,675
25	1	48	1,89	10	150				1,540	1,035
32	1 1/4	55	2,17	10	150				1,830	1,230
38	1 1/2	60	2,36	10	150				2,080	1,400
51	2	73	2,87	10	150				2,630	1,770

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



750AA

喷砂管 10 bar (150 psi)

内胶层: 黑色导电 NR - 耐磨损

加强层: 两层高强度纤维线

外胶层: 黑色导电 SBR/NR - 耐磨损、耐臭氧 - 刺孔工艺

应用: 喷砂

安全系数: 3:1

温度范围: -30 °C +80 °C (-22 °F +176 °F)