

										
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
13	1/2	21	0,83	5	75				0,280	0,190
16	5/8	24	0,94	5	75				0,330	0,225
18	23/32	26	1,02	5	75				0,360	0,245
20	13/16	28	1,10	5	75				0,390	0,265
22	7/8	30	1,18	5	75				0,420	0,285
25	1	33	1,30	5	75				0,470	0,320
28	1 1/8	36	1,42	5	75				0,510	0,345
30	1 3/16	38	1,50	5	75				0,540	0,365
32	1 1/4	40	1,57	5	75				0,570	0,385
35	1 3/8	43	1,69	5	75				0,620	0,420
38	1 1/2	48	1,89	5	75				0,850	0,575
40	1 9/16	50	1,97	5	75				0,890	0,600
42	1 5/8	52	2,05	5	75				0,930	0,625
45	1 3/4	55	2,17	5	75				0,980	0,660
48	1 7/8	58	2,28	5	75				1,040	0,700
51	2	61	2,40	5	75				1,110	0,750
55	2 1/6	65	2,56	5	75				1,180	0,795
57	2 1/4	67	2,64	5	75				1,220	0,820
60	2 3/8	70	2,76	5	75				1,280	0,865
63	2 1/2	73	2,87	5	75				1,340	0,905
70	2 3/4	80	3,15	5	75				1,440	0,970
76	3	86	3,39	5	75				1,550	1,045
80	3 1/8	90	3,54	5	75				1,630	1,100
90	3 1/2	102	4,02	5	75				2,010	1,355
102	4	114	4,49	5	75				2,250	1,515
110	4 5/16	122	4,80	5	75				2,410	1,620
115	4 1/2	127	5,00	5	75				2,510	1,690
127	5	141	5,55	5	75				3,200	2,155
NA		LA		NEU		EMEA		SA	AP	AU



352AA

散热器管 5 bar (75 psi)

优于 DIN 73411 SAE 20R1 D-2

内胶层: 黑色 EPDM

加强层: 高强度纤维线

外胶层: 黑色 EPDM - 耐热、耐磨损、耐臭氧

应用: 散热器

安全系数: 3:1

温度范围: -40 °C +120 °C (-40 °F +248 °F)