

											
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
19	3/4	29	1,14	21	300	57	2,25	100	0,610	0,410	
25	1	35	1,38	17	250	75	3,00	100	0,760	0,515	
32	1 1/4	42	1,65	14	200	96	3,75	100	0,900	0,605	
38	1 1/2	48	1,89	10	150	114	4,50	100	1,030	0,695	
51	2	61	2,40	7	100	153	6,00	100	1,330	0,895	
63	2 1/2	75	2,95	4	60	189	7,50	100	2,080	1,400	
76	3	88	3,46	4	60	228	9,00	100	2,480	1,670	
90	3 1/2	104	4,09	3	45	270	10,50	100	3,050	2,050	
102	4	116	4,57	2	30	306	12,00	100	3,410	2,295	
NA		LA		NEU		EMEA		SA		AP	AU



604AA

吸油和回油管

优于 SAE 100R4

内胶层: 黑色导电 NBR

加强层: 两层高强度纤维线并嵌有螺旋钢丝

外胶层: 黑色 CR - 耐磨损、耐臭氧、耐烃类化合物

应用: 液压系统的吸油和回油

安全系数: 4:1

温度范围: -40 °C +100 °C (-40 °F +212 °F)