

// 753AA



EVOLUTION

喷砂 - 高品质 - 12 bar (180 psi)

内胶层: 黑色导电NR - 耐磨损-50mm3 (ISO 4649/A)

加强层: 高强度纤维线

外胶层: 黑色SBR/NR - 耐磨损、耐臭氧 - 表皮刺孔

应用: 喷砂, 适合恶劣工况

常规运行温度范围: -40° C +80° C (-40° F +176° F)

													
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
19,0	3/4"	33,00	1,30	12	180	36	540				0,690	0,47	
19,0	3/4"	38,00	1,50	12	180	36	540				0,980	0,66	
19,0	3/4"	40,00	1,57	12	180	36	540				1,110	0,75	
25,0	1"	39,00	1,54	12	180	36	540				0,840	0,57	
25,0	1"	48,00	1,89	12	180	36	540				1,510	1,02	
32,0	1 1/4"	48,00	1,89	12	180	36	540				1,230	0,83	
32,0	1 1/4"	55,00	2,17	12	180	36	540				1,800	1,21	
38,0	1 1/2"	55,00	2,17	12	180	36	540				1,460	0,99	
38,0	1 1/2"	60,00	2,36	12	180	36	540				1,850	1,25	
51,0	2"	71,00	2,80	12	180	36	540				2,110	1,42	
51,0	2"	73,00	2,87	12	180	36	540				2,360	1,59	
51,0	2"	76,00	2,99	12	180	36	540				2,840	1,91	