

											
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
13	1/2	22	0,87	40	600	65	2,50		0,410	0,280	
19	3/4	28	1,10	40	600	95	4,00		0,540	0,365	
25	1	34	1,34	40	600	125	5,00		0,690	0,465	
32	1 1/4	42	1,65	40	600	160	6,50		1,070	0,720	
38	1 1/2	48	1,89	40	600	190	7,50		1,270	0,855	
51	2	64	2,52	40	600	255	10,00		1,990	1,340	
63	2 1/2	77	3,03	30	450	315	12,50		2,430	1,635	
76	3	90	3,54	30	450	380	15,00		2,900	1,950	
102	4	118	4,57	30	450	510	20,00		4,100	2,751	
NA		LA		NEU		EMEA		SA		AP	AU



140AK 压缩空气管 40 bar (600 psi) 钢丝编织

内胶层: 黑色 SBR - 耐油雾

加强层: 高强度钢丝编织

外胶层: 黄色 SBR - 耐磨损、耐臭氧、耐烃类化合物 - 刺孔工艺

应用: 高压空气, 适合恶劣工况 (矿山、采石场), 具有更久的使用寿命和更高的安全系数

安全系数: 4:1

温度范围: -30 °C +80 °C (-22 °F +176 °F)