

										
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
25	1			7	100	100	4,00	90	0,410	0,275
32	1 1/4			7	100	128	5,00	90	0,600	0,405
38	1 1/2			7	100	152	6,00	90	0,700	0,475
51	2			5	75	204	8,00	90	1,000	0,675
60	2 3/8			5	75	240	9,50	90	1,280	0,865
63	2 1/2			5	75	252	10,00	90	1,340	0,905
76	3			5	75	304	12,00	90	1,750	1,180
80	3 1/8			5	75	320	12,50	90	1,840	1,240
90	3 1/2			4	60	360	14,00	90	2,260	1,520
102	4			4	60	408	16,00	90	2,700	1,815
110	4 5/16			4	60	440	17,50	90	3,100	2,085
120	4 3/4			4	60	480	19,00	90	3,600	2,420
127	5			4	60	508	20,00	90	3,800	2,555
152	6			3	45	608	24,00	90	4,850	3,260
203	8			3	45	812	32,00	90	9,100	6,120
NA		LA		NEU		EMEA		SA	AP	AU



267BE

泥水吸排管 - PVC - 中等工况 超弹性

结构: 灰色 PVC 带有蓝色螺旋条纹 - 耐磨损、耐臭氧

加强层: 白色抗震硬质 PVC

应用: 吸水 and 排水。

适用于泥浆灌装车, 低温时具有好的柔性

安全系数: 3:1

温度范围: -20 °C +60 °C (-4 °F +140 °F)