

// 956 EVOLUTION



EXTRUDED
TUBE

General purpose 20 bar (300 psi) - EPDM

Tube: black conductive EPDM.

Reinforcement: high tensile textile braid up to ID 25mm - ID>32mm spiralled.

Cover: black conductive EPDM (956AA) - abrasion and ozone resistant. ID≤25mm smooth finish, ID>32mm wrapped.

Also available in red (956AH) and blue (956AE).

Application: general purpose hose.

Also suitable for cooling systems.

Temperature: -40 °C +120 °C (-40 °F +248 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Weight (kg/m)	Weight (lb/ft)
6,0	1/4"	13,0	0,51	20	300	80	1200	30,0	1,18	0,125	0,08
8,0	5/16"	15,0	0,59	20	300	80	1200	40,0	1,57	0,150	0,10
10,0	3/8"	17,0	0,67	20	300	80	1200	50,0	1,97	0,190	0,13
13,0	1/2"	21,0	0,83	20	300	80	1200	65,0	2,56	0,270	0,18
16,0	5/8"	25,0	0,98	20	300	80	1200	80,0	3,15	0,340	0,23
19,0	3/2"	28,0	1,10	20	300	80	1200	95,0	3,74	0,402	0,27
25,0	1"	35,0	1,38	20	300	80	1200	125,0	4,92	0,560	0,38
32,0	1 1/4"	44,0	1,73	20	300	60	900	160,0	6,30	0,760	0,51
38,0	1 1/2"	50,0	1,97	20	300	60	900	190,0	7,48	0,880	0,59
51,0	2"	64,0	2,52	20	300	60	900	255,0	10,04	1,230	0,83