// SEWERJET EVO NEW

Sewer hose 250 bar (3625 psi) - Textile braids

Tube: oil, detergents and hot water resistant synthetic rubber.
Reinforcement: two/three high tensile textile braids.
Cover: smooth. Abrasion, ozone and very low sliding resistance black synthetic rubber.
Application: sewer jetting and heavy duty, high pressure water cleaning; extremely flexible.
Temperature: -30 °C +80 °C (-22 °F +176 °F)
Length: tollerance ± 1% (norm ISO 1307).
Notes: a dedicated fittings range ensures high safety level. Hose can be supplied assembled with BSP female / BSP male in fixed lengths, pressure tested according to EN 10204 3.1 B.

Item Code	Constr.	ID (Dash)	ID (mm)	ID (in)	OD (mm)	OD (in)	WP (Mpa)	WP (psi)	BP (Mpa)	BP (psi)	BR (mm)	BR (in)	Weight (kg/m)	Weight (lb/ft)	Length (m)
1004972	2TB	8	13,0	1/2"	24,0	0,94	25,0	3630	62,5	9050	70	2,76	0,410	0,28	40,000
1003959	2TB	8	13,0	1/2"	24,0	0,94	25,0	3630	62,5	9050	70	2,76	0,410	0,28	60,000
1003837	2TB	8	13,0	1/2"	24,0	0,94	25,0	3630	62,5	9050	70	2,76	0,410	0,28	80,000
1004082	2TB	8	13,0	1/2"	24,0	0,94	25,0	3630	62,5	9050	70	2,76	0,410	0,28	100,000
1003979	2TB	8	13,0	1/2"	24,0	0,94	25,0	3630	62,5	9050	70	2,76	0,410	0,28	120,000
1003764	2TB	12	19,0	3/4"	31,5	1,24	25,0	3630	62,5	9050	90	3,54	0,600	0,41	80,000
1003663	2TB	12	19,0	3/4"	31,5	1,24	25,0	3630	62,5	9050	90	3,54	0,600	0,41	100,000
1003980	2TB	12	19,0	3/4"	31,5	1,24	25,0	3630	62,5	9050	90	3,54	0,600	0,41	120,000
1003738	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	80,000
1003609	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	100,000
1003736	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	120,000
1005837	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	150,000
1005939	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	160,000
1005873	2TB	16	25,0	1"	38,0	1,50	25,0	3630	62,5	9050	120	4,72	0,708	0,48	200,000
1005920	3TB	20	32,0	1 1/4"	47,6	1,87	25,0	3630	62,5	9050	130	5,12	1,094	0,74	80,000
1005921	3TB	20	32,0	1 1/4"	47,6	1,87	25,0	3630	62,5	9050	130	5,12	1,094	0,74	100,000
1005916	3TB	20	32,0	1 1/4"	47,6	1,87	25,0	3630	62,5	9050	130	5,12	1,094	0,74	120,000
1005922	3TB	20	32,0	1 1/4"	47,6	1,87	25,0	3630	62,5	9050	130	5,12	1,094	0,74	150,000
1005923	3TB	20	32,0	1 1/4"	47,6	1,87	25,0	3630	62,5	9050	130	5,12	1,094	0,74	200,000

ALFAGOMMA SEWERJET EVO // MINETUFF // -12 3/4" (DN 19) WP 250 bar 8K2AA MADE IN ITALY

// NO SKIVE FERRULE FOR MULTISPIRAL AND STANDARD FITTINGS

Hose	Table n°	-08 DN 12 1/2"	-12 DN 19 3/4"	-16 DN 25 1"	-20 DN 32 1 1/4"
SEWERJET EVO	271	H1200FK0	H1200FK0	H1200FK0	H1200FK0
			H1300FK0	H1300FK0	

上海沣峻流体科技有限公司 - AG授权分销商
TEL:+86-21-58400374/58400394
FAX:+86-21-50182690
E-mail:fengjunfluid@163.com
ADD:上海市奉贤区浦卫公路6655号一号厂房
https://tiger-flex.com.cn/