

<i>Hose type</i> FLEXOR 6 HT		<i>Reference Specification</i> SAE 100 R6 - EN 854 R6	
<i>Hose application</i> LOW PRESSURE HYDRAULIC LINES,FUEL OIL,ANTIFREEZE SOLUTIONS,AIR AND WATER SPECIA			
<i>Construction tube</i> OIL RESISTANT SYNTHETIC RUBBER		<i>T°C range (fluid)</i> -40°C +135°C (T max air = +70°C)	
<i>Construction reinforcement</i> ONE HIGH TENSILE TEXTILE BRAID		<i>T°C range (ambient)</i> -40°C +135°C	
<i>Construction cover</i> ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER		<i>Change in length at WP</i> +2% -4%	
<i>Length</i> Random		<i>Adhesion Tube / Braid</i> 1,5-2,5 Kg/cm	
<i>Standard marking</i> ALFAGOMMA FLEXOR 6 ID...- WP ... MPa (... PSI) - SAE 100R6-EN854 R6 -DN ... - Q/yr		<i>Adhesion Cover / Braid</i> 2-2,5 Kg/cm	
<i>Cover color</i> Black			

DIMENSIONS, PRESSURES, BEND RADIUS AND WEIGHT

PART NUMBER	DN	INCH	DASH	HOSE I.D.		WIRE O.D.		HOSE O.D.		BP	PP (bar)	WP	Min Bend Radius (mm)	Weight (kg/m)
				min (mm)	max (mm)	min (mm)	max (mm)	min (mm)	max (mm)					
808AA006	6			6.1	6.9			11.9	13.5	112	55	28	64	0.130
808AA008	8			7.6	8.4			13.5	15.1	112	55	28	76	0.150
808AA010	10			9.2	10.0			15.1	16.7	112	55	28	76	0.170
808AA012	12			12.4	13.3			19.0	20.6	112	55	28	102	0.230
808AA016	16			15.6	16.5			22.2	23.8	96	48	24	107	0.270
808AA020	20			18.7	19.8			25.4	27.8	84	42	21	152	0.370

Approvals

Notes

上海洋峻流体科技有限公司 - AG授权分销商

TEL:+86-21-58400374/58400394

FAX:+86-21-50182690

E-mail:fengjunfluid@163.com

ADD:上海市奉贤区浦卫公路6655号一号厂房

<https://tiger-flex.com.cn/>