



Platinum Cured Silicone Vacuum Hose

Technical description

Inner tube: High purity platinum cured Silicone
 Reinforcement: stainless steel helix and 3 layers of polyester reinforcement
 Cover: High purity platinum cured Silicone
 Temperature range: - 60 °C to + 200 °C.
 Standard/Approval:
 USP 23 CLASS VI.
 FDA 21 CFR 177.2600

Applications

- Pharmaceutical and Biotechnological processes
- Ultra-pure liquid transfer
- Food and beverage transfer
- Bulk transfer
- Load cell applications
- Vacuum applications

上海津峻流体科技有限公司 - AG授权分销商

TEL:+86-21-58400374/58400394

FAX:+86-21-50182690

E-mail:fengjunfluid@163.com

ADD:上海市奉贤区浦卫公路6655号一号厂房

<https://tiger-flex.com.cn/>

SILICONE RUBBER VACUUM HOSE - POLYESTER & WIRE REINFORCED (3PLY POLYESTER)

SIZE	I.D	O.D ± 0.6MM	WALL	BEND RADIUS	**WP 20 C BAR	** BP 20 C BAR
½"	12.7mm	22.5mm	4.9mm	75	10	30
¾"	19mm	28.8mm	4.9mm	85	10	30
1"	25.4mm	35.2mm	4.9mm	100	10	30
1 ¼"	31.8mm	41.6mm	4.9mm	120	10	30
1 ½"	38.1mm	47.9mm	4.9mm	145	10	30
2"	50.8mm	60.6mm	4.9mm	250	8	24
2 ½"	63.5mm	73.3mm	4.9mm	300	5	15
3"	76.2mm	86mm	4.9mm	460	3	9
4"	101.6mm	111.4mm	4.9mm	950	3	9

**** These are guide figures and should be confirmed by the manufacturer of the Assembly. (Re. fitting design)**