

// 400LE EVOLUTION



EXTRUDED
TUBE

2 x ID

2004/1831 EC
2006/2023 EC

PHTHALATE
& BPA FREE

Multi food S&D 10 bar (150 psi)

D.M. 21/03/1973 - ARRETE DU 05/08/2020 Cat. D

FDA - 3A SANITARY STANDARD

内胶层: 白色NBR

加强层: 高强度纤维线并嵌有螺旋钢丝

外胶层: 蓝色NBR/PVC - 耐磨损、耐臭氧

应用: 液态食品、脂肪类食品和酒精度不超过75%的酒精饮品的吸排。
超柔的特殊结构。用130 °C (266 °F) 水蒸汽消毒30分钟或用5%
的苏打水消毒

常规运行温度范围: 液态食品 -30°C +100°C (-22°F +212°F), 油脂
类食品高达 +120°C (248°F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Vacuum %	Weight (kg/m)	Weight (lb/ft)
25,0	1"	36,0	1,42	10	150	30	450	50	1,97	100,00	0,680	0,46
32,0	1 1/4"	43,0	1,69	10	150	30	450	64	2,52	100,00	0,900	0,61
38,0	1 1/2"	49,0	1,93	10	150	30	450	76	2,99	100,00	1,060	0,72
51,0	2"	63,0	2,48	10	150	30	450	102	4,02	100,00	1,470	0,99
63,0	2 1/2"	76,0	2,99	10	150	30	450	126	4,96	90,00	2,230	1,50
63,0	2 1/2"	78,0	3,07	10	150	30	450	126	4,96	90,00	2,450	1,65
76,0	3"	89,0	3,50	10	150	30	450	152	5,98	90,00	2,720	1,83
76,0	3"	91,0	3,58	10	150	30	450	152	5,98	90,00	2,940	1,98
102,0	4"	116,0	4,57	10	150	30	450	204	8,03	90,00	3,750	2,53
102,0	4"	119,0	4,69	10	150	30	450	204	8,03	90,00	4,040	2,72

ALFAGOMMA // 400 EVOLUTION // 10 bar (150 psi) MULTI FOOD S&D +100 °C (+212 °F) // AGFOOD // FDA 3-A DM SANITARY