

mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft	
20	13/16					20	0,75	50	0,130	0,087	
25	1					25	1,00	50	0,170	0,115	
32	1 1/4					32	1,25	50	0,230	0,155	
35	1 3/8					35	1,50	50	0,250	0,170	
40	1 9/16					40	1,50	40	0,300	0,200	
45	1 3/4					45	1,75	40	0,350	0,235	
51	2					51	2,00	40	0,440	0,300	
63	2 1/2					63	2,50	40	0,560	0,380	
70	2 3/4					70	2,75	40	0,630	0,425	
76	3					76	3,00	40	0,700	0,475	
80	3 1/8					80	3,00	40	0,760	0,515	
90	3 1/2					90	3,50	40	0,850	0,575	
102	4					102	4,00	40	0,990	0,670	
110	4 5/16					110	4,25	40	1,100	0,740	
120	4 3/4					120	4,75	40	1,200	0,810	
127	5					127	5,00	40	1,270	0,855	
140	5 1/2					140	5,50	35	1,450	0,975	
152	6					152	6,00	35	1,700	1,145	
160	6 5/16					160	6,25	35	1,850	1,245	
180	7 1/16					180	7,00	30	2,200	1,480	
203	8					203	8,00	30	2,450	1,650	
254	10					254	10,00	10	3,600	2,420	
305	12					305	12,00	10	4,500	3,025	
NA	LA	NEU	EMEA	SA	AP	AU					



161BL

通风管

UL 94 V2

结构: 灰色PVC - 耐磨损、耐臭氧

加强层: 白色抗震硬质PVC

应用: 抽取空气, 烟尘等气体。空调 - 通风管道

温度范围: -10 °C +60 °C (+14 °F +140 °F)